



AQUA-BAND

BUTYL RUBBER ELASTIC JOINT BAND FOR WATERPROOFING

DESCRIPTION

Aqua-Band is a wet area grade Elastic Joint Band designed for use in waterproofing wall/floor junctions of internal and external wet areas. Performs as the waterproofing system's bond breaker, avoiding the use of sealant beads and backing rod bond breaker methods. Also suitable for sealing movement joints and small expansion joint areas. Consists of a central rubber section with a flexible polyester fleece backing, suitable for use with liquid membranes.

Available in:

- 120mm x 50m rolls
- 10-packs of pre-made internal corners
- 10-packs of pre-made external corners
- 10-packs of 118mm x 118mm collars



PRODUCT FEATURES

- Rubber: NBR (acrylonitrile butadiene rubber)
- Carrier Edging: Polyester fleece with lateral flexibility
- Total Width: 120mm
- Thickness: 0.6-0.8mm
- Rubber width: 70mm span, 20mm central stretch zone
- Material weight: 50g/m.
- Surface face: Fleece lamination

PHYSICAL PROPERTIES

- Shore A hardness: 65
- Temperature Resistance: -20°C to 90°C
- Tensile strength (DIN 53504): >1.0 N/mm² lateral direction, >7.0 N/mm² longitudinal direction
- Rupture strain (DIN 53504): >208% lateral direction, >48% longitudinal direction
- Moisture vapour transmission resistance coefficient μ : 8.4
- Equivalent air thickness sd: 5.0m
- Water pressure resistance: 3 bar
- Fire Class (DIN, EN): B3, F

WARRANTY STATEMENT

ATA guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that this product is suitable for use and will perform as described in our technical data sheet or other published materials.

ATA will replace the product free of charge when purchased from any legally verifiable source and where the product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with relevant Australian Standards.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to ATA.

The consumer is responsible for any expenses incurred in making a claim.

Conditions of Sale contain a limited warranty against manufacturing defects.

A claim form can be requested by email or phone.

CONTACT DETAILS

Sales: customerservice@ata.com.au

0448 404 333

Technical: team@ata.com.au

0427 402 549

Other Enquiries: admin@ata.com.au

0416 921 087