



AQUA-STICK

SELF-ADHERING BUTYL RUBBER SHEET FOR WATERPROOFING

DESCRIPTION

Aqua-Stick 80 is a durable, self-adhering, butyl rubber sheet waterproof membrane with a polypropylene fleece backing, suitable for internal and external use.

Aqua-Stick 80 has excellent crack bridging capabilities and is suitable for use as a crack suppression membrane underneath tile or stone.

Aqua-Stick 80 is compatible with **Aus-Bond Ultra Prime**, as well as with all **Aqua-Flex**, **Aqua-Band**, **Aqua-Fab** and **Aqua-Stick** products.

Aqua-Stick 80 is a permanently flexible waterproof membrane that has excellent adhesion to a wide range of substrates (note that **Aus-Bond Ultra Prime** must be used on porous substrates before the application of **Aqua-Stick 80**).

Aqua-Stick 80 will bond to existing acrylic and SBR membranes, and nonporous substrates.

Aqua-Stick 80 has high resistance to aging, and it does not crack or craze due to its flexible properties.

Since **Aqua-Stick 80** is elastomeric it is not adversely affected by extreme temperatures. Consequently, it does not crack at low temperatures or suffer thermal flow at elevated temperatures. Suitable for hot or cold climates, will not break down or bleed.

Available in 80mm x 10m rolls.



BENEFITS

- Flexible membrane (100% + elongation).
- Eco-friendly. No odour for easy use without irritation.
- No drying required, can be tiled on immediately.
- Can be used both internally and externally.
- High resistance to aging.
- Compatible with good quality, polymer fortified, cement-based tile adhesives.
- Does not require reinforcing to be effective.
- Excellent crack-bridging properties. Suitable as a crack suppression membrane over hairline cracks of up to 2.5mm. For cracks over this size consult ATA.
- For use as a decoupling mat over problem substrates.
- Use over cold joints to prevent cracking.
- Bonds directly to PVC and other plumbing fixtures.
- **Aqua-Stick 80** will bond to **Aqua-Flex WPM C3**.