

AUS-BOND ACCELERATOR

LIQUID SETTING ACCELERANT FOR CEMENTITIOUS ADHESIVES

DESCRIPTION

Aus-Bond Accelerator Concentrate is a specially formulated liquid additive for use in cement based mortars to reduce the set times. **Aus-Bond Accelerator Concentrate** can be mixed with sand/cement, screeds, renders, cement-based tile adhesives and grouts. **Aus-Bond Accelerator Concentrate** can be mixed full strength for a fast set time, or it can be diluted with clean water for a slower set time. Set times will vary depending on temperature and the type of mix it is added to.

Caution: Aus-Bond Accelerator Concentrate is corrosive, and care should be taken when using this product.

Suitable for internal and external use.

Available in 5L and 20L.

MIXING

For best results mix diluted **Aus-Bond Accelerator Concentrate** into the mortar with a slow speed mixer, one that does not entrap air into the mix. Aus-Bond Accelerator Concentrate can be mixed with sand/cement mortars using a mechanical cement mixer. Do not over mix mortar.

SAFETY

Refer to the Safety Data Sheet for full, detailed instructions in accordance with the hazardous chemicals code of practice.

Aus-Bond Accelerator Concentrate is corrosive and care should be taken. Avoid breathing dust, wear an appropriate respirator and provide adequate ventilation. Avoid contact with skin and eyes, wear suitable gloves, eye protection and work wear when using all additives, latex, sand or cement-based products.



CLEANING

Remove excess adhesive or mortar with clean water while work proceeds. Hardened adhesive or mortars will be difficult to remove.

PRECAUTIONS & LIMITATIONS

Aus-Bond Accelerator Concentrate is corrosive and should not be used in conjunction with steel reinforcing, nor come into contact with steel on the jobsite. This adhesive or mortar may not be suitable for water sensitive tile or stone and some waterproof membranes such as full polyurethane, bitumen or torch on membranes. Always consult the manufacturer of these materials prior to starting the project. Do not use on tongue and groove timber or timber that is affected by moisture. In general, all timber should be overlaid with cement sheet prior to tiling or other applications. Always follow the installation instructions of the substrate supplier and Australian Standards.

Adhesives are affected by extremes of temperature. In hot weather conditions the adhesive will set fast and have a shorter open time; in cold conditions the adhesive will set slow requiring extended time prior to grouting and traffic. Do not use below 2°C and above 40°C. Structural failure and suitability of the substrate is outside of our control, care should be taken by the installer as starting the work constitutes acceptance of the substrate. Consult ATA if you have any questions.

WARRANTY STATEMENT

ATA guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

ATA will replace the product free of charge when purchased from any legally verifiable source and where the product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with relevant Australian Standards.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to ATA.

The consumer is responsible for any expenses incurred in making a claim.

Conditions of Sale contain a limited warranty against manufacturing defects.

A claim form can be requested by email or phone.

CONTACT DETAILS

Sales: customerservice@ata.com.au

0448 404 333

Technical: team@ata.com.au

0427 402 549

Other Enquiries: admin@ata.com.au

0416 921 087