



AUS-BOND GROUT & MORTAR ADMIX

LIQUID LATEX POROUS SUBSTRATE PRIMER AND ADMIX

DESCRIPTION

Aus-Bond Grout & Mortar Admix is a specially formulated, self-crosslinking latex acrylic additive for use as a primer for porous substrates prior to waterproofing, tiling or applying self-levelling mortars.

Aus-Bond Grout & Mortar Admix can be used with cement-based tile grouts to reduce water absorption, increase flexibility and help lock in colour. When used with cement-based tile adhesives, **Aus-Bond Grout & Mortar Admix** increases flexibility, promotes a permanent bond and increases water resistance.

Aus-Bond Grout & Mortar Admix can also be used as an additive to patching mortars, renders and screeds, as a slurry bond coat when mixed with Portland cement or cement-based tile adhesives, and as a primer prior to applying self-levelling mortars or waterproof membranes.

Suitable for internal and external use.

For best results do not dilute.

Available in 5L and 20L.

USES

- PRIMER FOR POROUS SUBSTRATES
- TILE ADHESIVES
- GROUTS
- SCREEDS
- RENDERS
- PATCHING MORTARS
- SLURRY BOND COATS

COVERAGE (per litre)

4 – 10 m²



SURFACE PREPARATION

All substrates must be clean and free from laitance, curing compounds, dirt, dust, grease, oil and any other contaminants that may inhibit bond. All substrates should be washed with clean water just prior to the application of the prepared mortar. **Aus-Bond Grout & Mortar Admix** can be applied to damp surfaces when mixed with the appropriate mortar. All grout joints must be free from spacers and construction debris prior to grouting.