

AUS-BOND POROUS PRIMER

WATER-BASED ACRYLIC PRIMER FOR POROUS SURFACES

DESCRIPTION

Aus-Bond Porous Primer is a cost-effective porous primer for use prior to installing ATA tile adhesives and waterproofing membranes. It increases adhesion while reducing dehydration over all porous substrates.

Aus-Bond Porous Primer is a safe alternative to hazardous solvent-based primers and etching products, which promotes the adhesion of a wide range of paints, coatings, membranes and adhesives to absorbent surfaces.

Suitable for internal and external use.

Available in 5L.

USES

- CEMENT
- CONCRETE BLOCKS
- SCREED AND RENDER
- MASONRY
- AERATED CONCRETE
- PLASTERBOARD
- FIBRE CEMENT SHEETING

COVERAGE (per litre)

8 – 10 m²



GENERAL APPLICATION

- Surfaces must be clean, sound and stable. Further, surfaces must be free of loose foreign material, existing coatings, laitance, release agents, curing compounds and oil/grease residue.
- Apply neat, do not dilute.
- Coverage of approximately 8-10m²/L, this may vary depending on surface porosity.
- Not suitable for solvent based finishes. Only use water-based systems over **Aus-Bond Porous Primer**.
- When applying the primer onto flooring, it is recommended to pour some primer in a section, then spread the primer using a broom, brush or roller. Continue this method until the entire area is primed. This application method ensures a thorough coat of the primer on the substrate.

IMPORTANT NOTES

- Not designed for use as an exposed or trafficable sealer.
- Not to be used for applications in immersed areas.
- Based on normal ambient conditions of 20°C, drying time is approximately 30 minutes before tiling/waterproofing can commence. Drying time may vary depending on substrate absorbency and climate conditions.
- Best storage conditions are in a dry area, off the ground and at room temperature. Avoid humidity and frost.
- While in a wet state, **Aus-Bond Porous Primer** will clean up with water. Once dried product will need to be removed by clean (or soapy) high pressure solutions.

SAFETY

Refer to the Safety Data Sheet for full, detailed instructions in accordance with the hazardous chemicals code of practice. Avoid contact with eyes and prolonged contact with skin. To avoid contact with skin and eyes wear protective clothing, goggles, gloves, safety shoes etc. If contact with eyes does occur, immediately flush with water and seek medical advice.

WARRANTY STATEMENT

ATA guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

ATA will replace the product free of charge when purchased from any legally verifiable source and where the product is proven to have been stored, handled, and installed according to instructions published on our packaging and within the stated shelf life. The installation of all materials must be carried out in accordance with relevant Australian Standards.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to ATA.

The consumer is responsible for any expenses incurred in making a claim.

Conditions of Sale contain a limited warranty against manufacturing defects.

A claim form can be requested by email or phone.

CONTACT DETAILS

Sales: customerservice@ata.com.au

0448 404 333

Technical: team@ata.com.au

0427 402 549

Other Enquiries: admin@ata.com.au

0416 921 087