



AUS-BOND ULTRA PRIME

SOLVENT-FREE NON-POROUS PRIMER

DESCRIPTION

Aus-Bond Ultra Prime is a unique, solvent free primer specifically designed with adhesion enhancing properties for use on metallic, smooth, dense, and non-porous surfaces. **Aus-Bond Ultra Prime** is a safe alternative to hazardous solvent-based primers and etching products, which enables the adhesion of a wide range of paints, coatings, membranes and adhesives over non-absorbent surfaces.

Suitable for internal and external use.

Available in 1L, 5L and 20L.



USES

- CEMENT BOARD
- DENSE CONCRETE
- GLAZED TILES
- PAINTED SURFACES
- PVC AND RIGID PLASTICS
- GALVANISED IRON, ZINCALUME, STAINLESS STEEL, COPPER & BRASS
- GENERAL NON-POROUS & SHINY SURFACES

COVERAGE (per litre)

8 – 12 m²

TECHNICAL NOTES (AT 21°C)

| | |
|------------------------|-------------------|
| SPECIFIC GRAVITY | 1.3kg/L |
| VISCOSITY | 4000 mPa·s |
| pH | 8 |
| APPEARANCE/COLOUR | ORANGE |
| WATER SOLUBILITY | 100% IN WET STATE |
| FLAMMABILITY | NIL |
| TEMPERATURE RESISTANCE | -20°C TO 80°C |



GENERAL APPLICATION

- Surfaces must be clean, sound and stable. Further, surfaces must be free of loose foreign material, existing coatings, laitance, release agents, curing compounds and oil/grease residue.
- **Aus-Bond Ultra Prime** should be lightly stirred before using, and can be applied to vertical, horizontal and overhead surfaces using a roller, brush or airless spray unit.
- Coverage of approximately 12m²/L, this may vary depending on surface porosity.
- Not suitable for solvent based finishes. Only use water-based systems over **Aus-Bond Ultra Prime**.
- Can be rendered or tiled over.

IMPORTANT NOTES

- Not designed for use as an exposed or trafficable sealer.
- Not to be used for applications in immersed areas.
- Based on normal ambient conditions of 23°C, drying times are:
 - Tack free – 15 minutes (will vary with surface porosity)
 - Dry film – 30 minutes.
- Best storage conditions are in a dry area at room temperature. Avoid humidity and frost.
- While in a wet state, **Aus-Bond Ultra Prime** will clean up with water. Once dried product will need to be removed by clean (or soapy) high pressure solutions.

SAFETY

Refer to the Safety Data Sheet for full, detailed instructions in accordance with the hazardous chemicals code of practice. Avoid contact with eyes and prolonged contact with skin. To avoid contact with skin and eyes wear protective clothing, goggles, gloves, safety shoes etc. If contact with eyes does occur, immediately flush with water and seek medical advice.

WARRANTY STATEMENT

ATA guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

ATA will replace the product free of charge when purchased from any legally verifiable source and where the product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with relevant Australian Standards.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to ATA.

The consumer is responsible for any expenses incurred in making a claim.

Conditions of Sale contain a limited warranty against manufacturing defects.

A claim form can be requested by email or phone.

CONTACT DETAILS

Sales: customerservice@ata.com.au

0448 404 333

Technical: team@ata.com.au

0427 402 549

Other Enquiries: admin@ata.com.au

0416 921 087