



# AUS-MASTIC

## PRE-MIXED D1 TILE ADHESIVE

### DESCRIPTION

**Aus-Mastic** is an acrylic based, flexible, pre-mixed internal wall tile adhesive with excellent non-slip properties designed for bonding tiles onto a variety of substrates like render, rendered brickwork, gyprock, plasterboard, and fibre cement sheet surfaces.

For use on internal walls only.

### COVERAGE (per 15L pail)

6 x 6 mm trowel
9.9 m <sup>2</sup>

### TECHNICAL NOTES (AT 21°C)

OPEN TIME	20 MINUTES
DRYING TIME	24 HOURS

### TECHNICAL NOTES (AT 28 DAYS)

SHEAR STRENGTH (SS)	≥ 1.00 MPa
SS, 14 DAYS HEAT AGED	≥ 1.00 MPa



### SURFACE PREPARATION

All substrates must be clean and free from laitance, curing compounds, dirt, dust, grease, oil and any other contaminants that may inhibit bond.

**Render:** All rendered surfaces must be allowed to cure for at least 7 days prior to commencing tiling.

**Fibre cement sheets:** Fibre cement sheet must be a minimum of 6mm in thickness and must be installed to the manufacturer's guidelines.

**Gypsum/Plasterboard sheets:** Gypsum and plasterboard sheet must be a minimum of 10mm thick and must be installed to the manufacturer's guidelines.