



TECHNICAL DATA SHEET

AUS-SEAL



TILE, GROUT, NATURAL STONE & MASONARY SEALER

PRODUCT DESCRIPTION

Aus-Seal is a sealer, for porous surfaces, it is an invisible, penetrating sealer that protects against stains, soiling, discoloration and efflorescence. It is clear, non-flammable solution which cures to an invisible water repellent coating. When used on grout joints, marble, granite, brick or porous tile it will reduce staining and water absorption. Will not change the colour of the tile, stone or grout.

USES

Use on interior and exterior surfaces to seal marble, granite, limestone, sandstone, terrazzo tile or insitu-terrazzo, ceramic tile and grout joints against soil and stains. Will help reduce efflorescence. Can be used as a grout release by treating ceramic tile or stone prior to grouting.



TECHNICAL DATA SHEET

AUS-SEAL

ADVANTAGES

- Protects grout joints from soil and stains.
- Reduces water absorption of tile grout, mortar, ceramic tile, brick & stone.
- Seals and protects ceramic tile, quarry tile, brick and stone.
- Permanent – one application is all that is needed for enduring protection.
- Weather resistant – protects tile and brick installations from weather and frost.
- Easy to apply – no special tools required.
- Water base – non-flammable.

SHELF LIFE

Factory sealed containers of this product are guaranteed to be of first quality for one (1) year if stored off the ground in a dry area.

LIMITATIONS

This is not a waterproof membrane. When a waterproof membrane is required, use Aqua-Flex, Aqua-Proof or Aqua-Stick.

CAUTIONS

- **Do not allow this product to dry on the surface.**
- **Clean off excess with a damp sponge or cloth.**
- **Do not use this product if the surface is non-porous.**
- **Protect aluminum and glass surfaces from direct prolonged exposure to sealer.**
- **Do not take Aus-Seal sealer internally. Wear a respirator when spraying this product.**
- **Keep out of reach of children.**
- **Aus-Seal, sealer is strongly alkaline.**
- **Protective gloves and eye protection should be worn when using this product**
- **Carry out a small test area to ensure a suitable outcome before applying to a large area**
- **The use of this product is beyond the control of ATA. Due to the variations in tile, stone and grout as well as the variables on jobsite conditions the suitability and use of this product relies on the experience of the applicator. ATA will not accept any responsibility for the use of this product. Carry out a test area and allow to cure for 48 hours to ensure suitability for the project.**

APPLICATION

Surface temperature should be between 7°C to 30°C. Allow grout and mortars to cure for 48 hours before applying sealer. Test a small unobtrusive area before coating entire surface.



TECHNICAL DATA SHEET

AUS-SEAL

The surface to be sealed must be clean and dry. Apply the sealer with a sponge, brush or sprayer. Allow to penetrate for 5 to 10 minutes. Wipe off excess sealer. A white residue may occur if excess material is allowed to dry on surface being treated. Allow sealer to cure for 24 hours. One application is sufficient for most installations. Very porous materials should have two applications. On heavy traffic areas or over long periods of time, reapply Aus-Seal sealer periodically.

CLEANING

Aus-Seal, sealer cleans easily with fresh water immediately after use.

Warranty:

“Australasian Tiling Adhesives Pty Ltd (“ATA”) warrants that **Aus-Seal** (“the goods”) will be free of defects for a period of up to **Ten years** from date of installation, subject to the goods being utilised and installed strictly in accordance with Australian Standards and industry guidelines. The use of the goods is beyond the control of ATA and/or the supplier and the liability of ATA under this warranty is restricted only to the replacement of the material found to be defective. Structural failure of the substrate is not covered by this warranty and the manufacturer and/or supplier of the goods will not be liable for any damage whatsoever arising from the incorrect use of the goods. A warranty claim must be made in writing by pre-paid registered post to ATA at PO Box 6468, Footscray West, 3012, Victoria [Tel: 0448 404 333] or by email to [admin@ata.com.au] by you within seven days of becoming aware of the defect. Proof of purchase by you, the date of purchase, and evidence of who installed the product, with relevant contact details, must accompany all claims. In the event of a dispute arising in relation to a claimed defect, ATA reserves the right to engage an independent expert to investigate and report, and the cost of the expert will be borne by the party at fault. The benefits to you given by this warranty are in addition to other rights and remedies you may have under any law in relation to the goods to which the warranty relates. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods replaced or repaired if the goods fail to be of acceptable quality and the failure does not amount to a major failure.”

Contact Details:

**Australasian Tiling Adhesives Pty Ltd (ATA), ABN: 92 154 228 207, ACN: 154 228 207,
Mobile: 0448 404 333, Email: admin@ata.com.au , Web: ata.com.au
PO Box 6468, Footscray West, Victoria 3012**

File: ACPIAW290715



TECHNICAL DATA SHEET

AUS-SEAL