



# AUS-CRETE MPA

**MULTI-PURPOSE ADHESIVE – C2TES1**

## DESCRIPTION

**Aus-Crete MPA** is a high performance, flexible, polymer fortified adhesive with excellent slip resistance that is used for installing a wide range of tile and stone. **Aus-Crete MPA** is made from graded aggregates and specialty fibres to reduce shrinkage. **Aus-Crete MPA** provides great coverage and is easy to use. **Aus-Crete MPA** will install tile and stone to a very wide range of substrates: cement sheet, plasterboard, suitable waterproof membranes, concrete, render and screeds.

Suitable for internal and external use.  
Available in white, off-white and grey.

Mix with Aus-Bond Industrial Latex Admix in place of water for heated floors and C2S2 performance.

## USES

- LARGE TILE AND STONE
- MARBLE AND GRANITE
- PORCELAIN
- QUARRY TILE AND CERAMICS
- MOSAIC AND GLASS TILE
- ALL MASONRY SURFACES
- RENDER, BRICK AND BLOCKWORK
- CEMENT SHEET AND PLASTERBOARD
- SUITABLE WATERPROOF MEMBRANES

## COVERAGE (per 20kg bag)

6 x 6 mm trowel	10 x 10 mm trowel
8 – 10 m <sup>2</sup>	6 – 7 m <sup>2</sup>



## TECHNICAL NOTES (AT 21°C)

<b>OPEN TIME</b>	<b>30 MINUTES</b>
<b>POT LIFE</b>	<b>2 HOURS</b>
<b>INITIAL SET</b>	<b>8 HOURS</b>
<b>FOOT TRAFFIC</b>	<b>24 HOURS</b>
<b>HEAVY TRAFFIC</b>	<b>72 HOURS</b>

## TECHNICAL NOTES (AT 28 DAYS)

<b>TENSILE STRENGTH (TS)</b>	<b>≥ 1.00 MPa</b>
<b>TS, 21 DAYS IMMERSUED</b>	<b>≥ 1.00 MPa</b>
<b>TS, 14 DAYS HEAT AGED</b>	<b>≥ 1.00 MPa</b>
<b>TRANSVERSE DEFORMATION</b>	<b>≥ 2.50 mm</b> <b>&lt; 5.00 mm</b>