



# AUS-CRETE MAX-LIGHT

FLEXIBLE LIGHTWEIGHT POLYMER REINFORCED ADHESIVE – C1TES1

## DESCRIPTION

**Aus-Crete Max-Light 9.5** is a high-performance mastic type that is a flexible and polymer fortified adhesive that is used for installing a wide range of tile and stone. **Aus-Crete Max-Light 9.5** provides great coverage and is exceptionally easy to use. **Aus-Crete Max-Light 9.5** will install tile and stone to a very wide range of substrates: cement sheet, plasterboard, suitable waterproof membranes, concrete, render and screeds. Suitable for packing out and back buttering to plumb and level tile and stone installations. This product will chemically cure when installing large porcelain tile over waterproof membranes.

Suitable for internal use only.

Mix with Aus-Bond Industrial Latex Admix in place of water for heated floors and C2S2 performance.

## USES

- LARGE TILE AND STONE
- MARBLE AND GRANITE
- PORCELAIN TILE
- QUARRY TILE AND MOSAIC TILE
- GLASS TILE AND MOSAIC
- ALL MASONRY SUBSTRATES
- RENDER, BRICK AND BLOCKWORK
- CEMENT SHEET AND PLASTERBOARD
- SUITABLE WATERPROOF MEMBRANES

## COVERAGE (per 20kg bag)

6 x 6 mm trowel	10 x 10 mm trowel
8 - 10 m <sup>2</sup>	6 m <sup>2</sup>



## TECHNICAL NOTES (AT 21°C)

OPEN TIME	30 MINUTES
POT LIFE	4 HOURS
INITIAL SET	8 HOURS
FOOT TRAFFIC	18 HOURS
HEAVY TRAFFIC	48 HOURS