



# AUS-FLEX PLATINUM

## POLYMER & RUBBER REINFORCED ADHESIVE – C1TES1

### DESCRIPTION

**Aus-Flex Platinum** is a high performance flexible polymer and rubber fortified adhesive that is used for installing a wide range of tile and stone.

**Aus-Flex Platinum** provides great coverage and is easy to use. **Aus-Flex Platinum** will install tile and stone to a wide range of substrates: existing ceramic tile, cement sheet, plasterboard, suitable waterproof membranes, concrete, render and screeds.

Suitable for internal and external use.

Mix with Aus-Bond Industrial Latex Admix in place of water for heated floors and C2S2 performance



### USES

- PORCELAIN TILE
- ALL MASONRY SURFACES
- CERAMIC TILE
- CONCRETE
- QUARRY TILE
- RENDER, BRICK AND BLOCK WORK
- MOSAIC TILE AND STONE
- CEMENT SHEET AND PLASTERBOARD
- MARBLE AND GRANITE
- SUITABLE WATERPROOF MEMBRANES

### COVERAGE (per 20kg bag)

6 x 6 mm trowel	10 x 10 mm trowel
8 – 10 m <sup>2</sup>	9 – 10 m <sup>2</sup>

### TECHNICAL NOTES (AT 21°C)

OPEN TIME	30 MINUTES
POT LIFE	2 HOURS
INITIAL SET	8 HOURS
FOOT TRAFFIC	24 HOURS
HEAVY TRAFFIC	72 HOURS

### TECHNICAL NOTES (AT 28 DAYS)

TENSILE STRENGTH (TS)	≥ 1.50 MPa
TS, 21 DAYS IMMERSSED	≥ 0.50 MPa
TS, 14 DAYS HEAT AGED	≥ 1.00 MPa
TRANSVERSE DEFORMATION	≥ 4.25 mm < 5.00 mm