



SCREED & RENDER (NORMAL)

POLYMER-MODIFIED SAND AND CEMENT MORTAR

DESCRIPTION

Aus-Crete Screed n' Render Normal Set provides a high performance, flexible, shock and vibration resistant polymer fortified cement-based screed or render mortar. **Aus-Crete Screed n' Render Normal Set** is easy to use, and suitable for thin screeds and levelling. **Aus-Crete Screed n' Render Normal Set** can be used under ceramic tile and stone, vinyl, wood or carpet, and is suitable as a preparation mortar prior to waterproofing. **Aus-Crete Screed n' Render Normal Set** can be used in permanent wet areas such as swimming pools and fountains, and for commercial/industrial floors and walls. **Aus-Crete Screed n' Render Normal Set** is also available in Fast Set.

USES

- INTERNAL AND EXTERNAL AREAS
- DRY, WET AND SUBMERGED APPLICATIONS
- OVER CONCRETE & RAW FIBRE CEMENT SHEET
- BONDED OR DIVORCED FLOORING SYSTEMS
- EXTRA HEAVY-DUTY INSTALLATIONS
- CONCRETE PATCHING

COVERAGE (per 20kg bag)

12mm thickness	5mm thickness
0.8 m ²	2 m ²



SURFACE PREPARATION

All substrates must be clean and free from laitance, curing compounds, dirt, dust, grease, oil and any other contaminants that may inhibit bond. All substrates should be washed with clean water just prior to the application of the adhesive. **Aus-Crete Screed n' Render Normal Set** can be applied to damp surfaces. Semi dry screed mortars require a wet slurry bond coat.