

FAST SET POWDER ADDITIVE

SETTING ACCELERANT FOR CEMENTITIOUS ADHESIVES

DESCRIPTION

Fast Set Powder Additive is a specially formulated additive for use in cement-based mortars to reduce the set times. **Fast Set Powder Additive** can be mixed with sand/cement, screeds, renders, cement-based tile adhesives and grouts. Set times will vary depending on temperature and the type of mix it is added to.

Caution: Fast Set Powder Additive is corrosive, and care should be taken when using this product.

Suitable for internal and external use.

Available in 10kg pail.



MIXING

Using the measuring cup provided, dissolve/dilute 500mL of the **Fast Set Powder Additive** into 4L of clean water. Then mix a 20kg bag of tile adhesive into solution.

Fast Set Powder Additive will reduce the pot life and open times of all cement-based tile adhesives by speeding up the setting process. Set times will vary depending on site conditions, the design of the mortar mix and the type of installation. In general, the tile adhesive will set in half the normal setting time.

CLEANING

Remove excess adhesive or mortar with clean water while work proceeds. Hardened adhesive or mortars will be difficult to remove.

SAFETY

Fast Set Powder Additive is corrosive and care should be taken. Avoid breathing dust, wear an appropriate respirator and provide adequate ventilation. Avoid contact with skin and eyes, wear suitable gloves, eye protection and work wear when using all additives and tile adhesives.

PRECAUTIONS & LIMITATIONS

Fast Set Powder Additive is corrosive and should not be used in conjunction with steel reinforcing, nor come into contact with steel on the jobsite. Adhesive mixed with **Fast Set Powder Additive** will set very fast in hot weather. When not in use, keep the bucket sealed to ensure the powder is not exposed to the air. Clean all equipment exposed to the powder thoroughly with water after use.

Contact ATA if you have any questions.

WARRANTY STATEMENT

ATA guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

ATA will replace the product free of charge when purchased from any legally verifiable source and where the product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with relevant Australian Standards.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to ATA.

The consumer is responsible for any expenses incurred in making a claim.

Conditions of Sale contain a limited warranty against manufacturing defects.

A claim form can be requested by email or phone.

CONTACT DETAILS

Sales: customerservice@ata.com.au

0448 404 333

Technical: team@ata.com.au

0427 402 549

Other Enquiries: admin@ata.com.au

0416 921 087