



LUMINOUS SSG GROUT

SUPER SMOOTH GROUT

DESCRIPTION

RLA LUMINOUS SSG is a high performance ceramic tile grout designed for internal and external applications. With enhanced workability, the smooth finish and built-in water and mould resistance improves colour fastness, vibrancy and overall durability for demanding environments.

Luminous SSG is available in a range of colours to suit various design preferences.

Compatible with underfloor heating systems.

Available in 4kg and 10kg bags.



USES

- PORCELAIN TILE
- CERAMIC TILE
- TERRAZZO
- SLATE AND QUARRY TILE
- GLASS
- MOSAIC TILE AND STONE
- NATURAL STONE (NON-MOISTURE SENSITIVE)

COVERAGE

Please see the RLA Polymers grout coverage calculator at www.rlapolymers.com.au/luminous-grout-calculator/ to estimate grout coverage based on tile size, joint width and area to be grouted.

TECHNICAL DATA

COLOURS	ASSORTED
MIX RATIO	240ml of water per kg 960ml per 4kg 2.4 litres per 10kg

APPLICATION DATA

23° @ 50% RH

POT LIFE	45 MINUTES TO 1 HOUR
DRYING TIME	LIGHT FOOT TRAFFIC: 24 HR FULL SERVICE: 3 DAYS
APPLICATION TEMPERATURE	+ 5°C to +35°C