



TECHNICAL DATA SHEET

ULTRA PRIME



Solvent free primer specially designed with adhesion enhancing properties for non-absorbent surfaces. A safe alternative to hazardous solvent-based primers and etching products that is fast drying and water resistant.

Available in:
1L jug, 5L & 20L bucket

Internal & external use.

Suitable for priming over:

- Wet-area cement board
- Dense concrete
- Glazed tiles
- Painted surfaces
- PVC and rigid plastics
- Galvanised iron, zincalume, stainless steel, copper & brass
- General non-porous and shiny surfaces

Coverage per 1L
8 - 12 m ²

Product Overview:

Aus-Bond Ultra Prime is a unique, solvent free primer specifically designed with adhesion enhancing properties for use on metallic, smooth, dense, and non-porous surfaces. **Aus-Bond Ultra Prime** is a safe alternative to hazardous solvent-based primers and etching products, which enables the adhesion of a wide range of paints, coatings, membranes and adhesives over non-absorbent surfaces.

Product Features:

- Solvent free, non-flammable and free of hazardous odours.
- Suitable for internal and external priming applications.
- Fast drying.
- Excellent water resistance.
- Alternative to grinding and etching surfaces.



TECHNICAL DATA SHEET

ULTRA PRIME

TECHNICAL NOTES:

SPECIFIC GRAVITY OF MIXED PRODUCT	1.3kg/L
VISCOSITY	4000 mPa·s
pH	8
APPEARANCE	ORANGE
WATER SOLUBLE	100% SOLUBLE IN A WET STATE
FLAMMABILITY	NIL
TEMPERATURE RESISTANCE	-20°C TO 80°C

General Application Details:

- Surfaces must be clean, sound and stable. Further, surfaces must be free of loose foreign material, existing coatings, laitance, release agents, curing compounds and oil/grease residue.
- **Aus-Bond Ultra Prime** should be lightly stirred before using, and can be applied to vertical, horizontal and overhead surfaces using a roller, brush or airless spray unit.
- Coverage of 12m²/L, this may vary depending on surface porosity.
- Not suitable for solvent based finishes. Only use water based systems over **Aus-Bond Ultra Prime**.
- Can be rendered or tiled over.

Important Notes:

- Not designed for use as an exposed or trafficable sealer.
- Not to be used for applications in immersed areas.
- Based on normal ambient conditions of 23°C, drying times are:
 - Tack free – 15 minutes (will vary with surface porosity),
 - Dry film – 30 minutes.
- Best storage conditions are in a dry area at room temperature. Avoid humidity and frost.
- While in a wet state, **Aus-Bond Ultra Prime** will clean up with water. Once dried product will need to be removed by clean (or soapy) high pressure solutions.

Packaging:

Available in 1, 5 and 20L pails.

Warranty:

“Australasian Tiling Adhesives Pty Ltd (“ATA”) warrants that **Aus-Bond Ultra Prime** (“the goods”) will be free of defects for a period of up to **Ten years** from date of installation,



TECHNICAL DATA SHEET

ULTRA PRIME

subject to the goods being utilised and installed strictly in accordance with Australian Standards and industry guidelines. The use of the goods is beyond the control of ATA and/or the supplier and the liability of ATA under this warranty is restricted only to the replacement of the material found to be defective. Structural failure of the substrate is not covered by this warranty and the manufacturer and/or supplier of the goods will not be liable for any damage whatsoever arising from the incorrect use of the goods. A warranty claim must be made in writing by email to [\[admin@ata.com.au\]](mailto:admin@ata.com.au) by you within seven days of becoming aware of the defect. Proof of purchase by you, the date of purchase, and evidence of who installed the product, with relevant contact details, must accompany all claims. In the event of a dispute arising in relation to a claimed defect, ATA reserves the right to engage an independent expert to investigate and report, and the cost of the expert will be borne by the party at fault. The benefits to you given by this warranty are in addition to other rights and remedies you may have under any law in relation to the goods to which the warranty relates. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods replaced or repaired if the goods fail to be of acceptable quality and the failure does not amount to a major failure.”

Contact Details:

**Australasian Tiling Adhesives Pty Ltd (ATA), ABN: 92 154 228 207, ACN: 154 228 207,
Mobile: 0448 404 333, Email: admin@ata.com.au , Web: ata.com.au**